TECHNICAL DATA SHEET

ALab™ DispensMate-E Bottle-Top Dispenser

Bottle-top dispenser · 1 to 60 mL · four volume ranges · safety shut-off valve



ALab™ DispensMate-E Bottle-Top Dispenser

The ALab™ DispensMate-E bottle-top dispenser; image shown for reference.

CONTENTS

01 Product Overview

02 Core Advantages

03 Specifications

04 Applications

ACS MATERIAL, LLC

959 E Walnut St., Suite 100

Pasadena, CA 91106, USA

Phone +1 (866) 227-0656

Fax +1 (781) 518-0284

contact@acsmaterial.com

Revision Date **10/22/2026**

SECTION I

Product Overview

The ALab™ DispensMate-E Bottle-Top Dispenser is a simple dispenser for routine liquid dispensing, available in four published volume ranges from 1–5 mL to 10–60 mL. A digital volume window with a gear slot design, a floating piston and a safety shut-off valve make dispensing accurate, smooth and safe.

The tube end safety cap stops residual liquid from flowing out, and five bottle neck adapters are included to fit reagent bottles of different sizes. The dispenser has excellent chemical resistance and is easy and economical to clean and maintain.

SECTION II

Core Advantages

- **Volume** — digital window, gear slot
- **Safety** — shut-off valve
- **Bottles** — five adapters included
- **Piston** — floating, smooth action
- **Discharge** — tube end safety cap
- **Care** — easy cleaning

SECTION III

Specifications

Technical data — DispensMate-E

Specifications	
Brand	ALab™ by ACS Material
Model	DispensMate-E
SKU #	Parent ALDISE00; ALDISE02 to ALDISE05
Product type	Bottle-top dispenser
Volume ranges	1–5, 2–10, 5–30, 10–60 mL
Volume setting	Rotating scale adjustment knob, digital window
Materials	PTFE, FEP, PVC, PP
Bottle neck adapters	S40 (45/40 mm), GL32 (45/32 mm), GL38 (45/38 mm), GL25 (32/25 mm), GL28 (32/28 mm)
Maximum pressure	500 mbar
Maximum viscosity	500 mm^2/s
Maximum liquid temperature	40°C
Maximum liquid density	2.2 g/cm^3
Safety features	Safety shut-off valve; tube end safety cap

Volume ranges and accuracy

Range (mL)	Grad. (mL)	Test vol. (mL)	Syst. (±%)	Syst. (±µL)	Random (±%)	Random (±µL)
1–5	0.1	1	5	50	1	10
1–5	0.1	2.5	1	25	0.2	5
1–5	0.1	5	0.5	25	0.1	5
2–10	0.2	2	5	100	1	20
2–10	0.2	5	1	50	0.2	10
2–10	0.2	10	0.5	50	0.1	10
5–30	0.5	5	5	250	1	50
5–30	0.5	15	1	150	0.2	30
5–30	0.5	30	0.5	150	0.1	30
10–60	1	10	5	500	1	100
10–60	1	30	1	300	0.2	60
10–60	1	60	0.5	300	0.1	60

Systematic and random error values are shown at the test volumes listed for each range.

Scope of delivery

— Standard configuration: DispensMate-E bottle-top dispenser of the selected volume range, with S40, GL32, GL38, GL25 and GL28 bottle neck adapters.

SECTION IV

Applications

Routine liquid dispensing directly from the reagent bottle in chemistry, biology, pharmaceuticals, food, environmental monitoring, and scientific research and education.

Choose the range by the volume dispensed and keep within the liquid limits (500 mbar, 500 mm^2/s, 40°C, 2.2 g/cm^3); check chemical compatibility for the intended reagent.

Revision Date: 10/22/2026

DISCLAIMER

ALab™ is a trademark of ACS Material, LLC. ACS Material, LLC believes that the information in this Technical Data Sheet is accurate and represents the best and most current information available to us. ACS Material makes no representations or warranties, either express or implied, regarding the suitability of the equipment for any application or the accuracy of the information contained within this document. Specifications are typical and may vary by model; assess product details and application suitability for the intended use. Accordingly, ACS Material will not be responsible for damages resulting from use of or reliance upon this information.