TECHNICAL DATA SHEET

ALab™ DispensMate-Pro Bottle-Top Dispenser

Bottle-top dispenser · 0.5 to 100 mL · five volume ranges · autoclavable at 121°C



ALab™ DispensMate-Pro Bottle-Top Dispenser

The ALab™ DispensMate-Pro bottle-top dispenser; image shown for reference.

CONTENTS

01 Product Overview

02 Core Advantages

03 Specifications

04 Applications

ACS MATERIAL, LLC

959 E Walnut St., Suite 100

Pasadena, CA 91106, USA

Phone +1 (866) 227-0656

Fax +1 (781) 518-0284

contact@acsmaterial.com

Revision Date **10/22/2026**

SECTION I

Product Overview

The ALab™ DispensMate-Pro is a bottle-top dispenser for dispensing directly from the bottle, in five volume ranges from 0.5 mL to 100 mL. Every range has a systematic error of ±0.5% and a random error of ±0.2%.

The volume is set and locked on a clear scale, the reagent recovery function reduces reagent waste and prevents dripping, and the aspirating tube adjusts to different bottle heights. The dispenser uses inert materials and a glass/PTFE piston. It is easy to disassemble and clean and is fully autoclavable at 121°C.

SECTION II

Core Advantages

- **Volume** — locking mechanism, clear scale
- **Bottles — adapters for common neck sizes**
- **Autoclavable** — 121°C
- **Reagent** — recovery function, no dripping
- **Materials** — inert, glass/PTFE piston
- **Accuracy** — ±0.5% / ±0.2%

SECTION III

Specifications

Technical data — DispensMate-Pro

Specifications	
Brand	ALab™ by ACS Material
Model	DispensMate-Pro
ACS Cat. No.	Parent ALDSPP; ALDSPP01 to ALDSPP05
Product type	Bottle-top dispenser
Volume ranges	0.5 to 5, 1.0 to 10, 2.5 to 25, 5.0 to 50 and 10 to 100 mL
Systematic error	±0.5% (all ranges)
Random error	±0.2% (all ranges)
Materials	Inert materials, glass/PTFE piston
Volume setting	Volume locking mechanism on a clear scale
Reagent recovery	Yes, reduces reagent waste and prevents dripping
Aspirating tube	Adjustable for different bottle heights
Sterilization	Fully autoclavable at 121°C

Volume ranges and accuracy

Volume range (mL)	Graduation (mL)	Syst. error (µL)	Syst. error (%)	Random error (µL)	Random error (%)	ACS Cat. No.
0.5 to 5	0.1	±25	±0.5	±10	±0.2	ALDSPP01
1.0 to 10	0.2	±50	±0.5	±20	±0.2	ALDSPP02
2.5 to 25	0.5	±125	±0.5	±50	±0.2	ALDSPP03
5.0 to 50	1.0	±250	±0.5	±100	±0.2	ALDSPP04
10 to 100	2.0	±500	±0.5	±200	±0.2	ALDSPP05

Adapters and accessories

Accessory	Status
GL32 adapter, 45/32 mm	Listed
GL38 adapter, 45/38 mm	Listed
GL25 adapter, 32/25 mm	Listed
GL28 adapter, 32/28 mm	Listed
S40 adapter, 45/40 mm	Listed
Reagent bottle, brown, 1 L	Listed
Filling tube combination	Listed
Discharge tube (for 25, 50 and 100 mL)	Listed
Discharge tube (for 5 and 10 mL)	Listed
Discharge tube combination (for 25, 50 and 100 mL)	Listed
Discharge tube combination (for 5 and 10 mL)	Listed

Scope of delivery

— Standard configuration: DispensMate-Pro bottle-top dispenser of the selected volume range.

SECTION IV

Applications

Suited to routine dispensing of reagents and solvents directly from the bottle, where a locked volume, low reagent waste and no dripping matter.

Choose the range by the volume dispensed. Check chemical compatibility for the intended reagent and concentration. Specifications are per the tables above.

Revision Date: 10/23/2026

DISCLAIMER

ALab™ is a trademark of ACS Material, LLC. ACS Material, LLC believes that the information in this Technical Data Sheet is accurate and represents the best and most current information available to us. ACS Material makes no representations or warranties, either express or implied, regarding the suitability of the equipment for any application or the accuracy of the information contained within this document. Specifications are typical and may vary. Assess application suitability for the intended use. Accordingly, ACS Material will not be responsible for damages resulting from use of or reliance upon this information.