TECHNICAL DATA SHEET

ALab™ DMS5-340M Magnetic Hotplate Stirrer

LCD digital 5-inch timed heating magnetic stirrer · strong magnetic · RT to 340°C · 50 to 1500 rpm



ALab™ DMS5-340M Magnetic Hotplate Stirrer

The ALab™ DMS5-340M magnetic hotplate stirrer; image shown for reference.

CONTENTS

01 Product Overview

02 Core Advantages

03 Specifications

04 Applications

ACS MATERIAL, LLC

959 E Walnut St., Suite 100

Pasadena, CA 91106, USA

Phone +1 (866) 227-0656

Fax +1 (781) 518-0284

contact@acsmaterial.com

Revision Date **10/22/2026**

SECTION I

Product Overview

The ALab™ DMS5-340M is an LCD digital 5-inch timed heating magnetic stirrer with a strong magnetic field for viscous samples. Its Ø135 mm ceramic-coated aluminum plate heats from RT to 340°C in 1°C increments, and a brushless DC motor stirs at 50 to 1500 rpm with a maximum stirring volume of 20 L of water.

One LCD shows speed, time and temperature. A PT1000 external temperature sensor (accuracy ±0.2°C) measures the liquid; three heating modes, a settable safety temperature, 420°C overheating protection, two independent safety circuits and a "HOT" residual-heat warning cover heating safety, and RS232 allows PC remote control. The corrosion-resistant all-metal housing provides heat dissipation and fire protection.

SECTION II

Core Advantages

- **Stirring** — strong magnetic field, viscous samples
- **Heating** — RT to 340°C, modes A / B / C
- **Timer** — heating stops, stirring continues
- **Plate** — Ø135 mm, ceramic-coated aluminum
- **Sensor** — PT1000, ±0.2°C
- **Safety** — two independent safety circuits

SECTION III

Specifications

Technical data — DMS5-340M

Specifications	
Brand	ALab™ by ACS Material
Model	DMS5-340M
ACS Cat. No.	ALMS534M (parent ALMS5)
Product type	LCD digital 5-inch timed heating magnetic stirrer (strong magnetic)
Working plate size	Ø135 mm (5 inch)
Plate material	Aluminum with ceramic coating
Motor type	Brushless DC motor
Stirring positions	1
Maximum stirring volume [H_2O]	20 L
Maximum stirrer size [length]	80 mm
Speed range and step	50 to 1500 rpm, increment 1 rpm
Speed display	LCD
Temperature display	LCD
Heating temperature range	RT to 340°C, increment 1°C
Temperature control accuracy of heating liquid	±1°C (<100°C), ±1% (>100°C)
Overheating protection	420°C
Temperature display accuracy	±0.1°C
External temperature sensor	PT1000 (accuracy ±0.2°C)
Residual heat warning	50°C
Data connection	RS232
Protection class	IP42
Timer function	1 min to 99 h 59 min
Motor output power	10 W
Power	650 W
Heating output power	600 W

Specifications	
Voltage, frequency	100 to 120 V / 200 to 240 V, 50/60 Hz
Dimensions [L × W × H]	270 × 175 × 98 mm
Weight	2.2 kg
Permissible ambient temperature and humidity	5 to 40°C, 80% RH

SECTION IV

Applications

The DMS5-340M is suitable for stirring viscous liquids and for general chemical synthesis. The specified maximum stirring volume is 20 L of water. A PT1000 external sensor supports liquid-temperature control, mode C provides stable heating, and RS232 supports PC remote control.

Specifications are per the table above.

Revision Date: 10/23/2026

DISCLAIMER

ALab™ is a trademark of ACS Material, LLC. ACS Material, LLC believes that the information in this Technical Data Sheet is accurate and represents the best and most current information available to us. ACS Material makes no representations or warranties, either express or implied, regarding the suitability of the equipment for any application or the accuracy of the information contained within this document. Specifications are typical and may vary. Assess application suitability for the intended use. Accordingly, ACS Material will not be responsible for damages resulting from use of or reliance upon this information.