TECHNICAL DATA SHEET

ALab™ DMS7 LCD Digital 7-Inch Magnetic Stirrer

LCD digital magnetic stirrer · 184 × 184 mm glass-ceramic plate · 50 to 1500 rpm · 20 L · timer · RS232



ALab™ DMS7 LCD Digital 7-Inch Magnetic Stirrer

The ALab™ DMS7 LCD Digital 7-Inch Magnetic Stirrer; image shown for reference.

CONTENTS

01 Product Overview

02 Core Advantages

03 Specifications

04 Applications

ACS MATERIAL, LLC

959 E Walnut St., Suite 100

Pasadena, CA 91106, USA

Phone +1 (866) 227-0656

Fax +1 (781) 518-0284

contact@acsmaterial.com

Revision Date **10/23/2026**

SECTION I

Product Overview

The ALab™ DMS7 is an LCD digital magnetic stirrer with a 7-inch (184 × 184 mm) glass-ceramic plate. It stirs up to 20 L of water at 50 to 1500 rpm in 1 rpm steps, with stirrer bars up to 80 mm. It has no heater.

The brushless DC motor is maintenance free. The LCD shows set and actual speed and time; the timer runs from 1 min to 99 h 59 min with a buzzer at the end. A safety lock, a waterproof plate edge, a corrosion-resistant all-metal housing and an RS232 connector for remote PC control complete the unit.

SECTION II

Core Advantages

- **Plate** — 184 × 184 mm glass ceramic
- **Volume** — up to 20 L [H_2O]
- **Safety** — safety lock, buzzer
- **Speed** — 50 to 1500 rpm, 1 rpm steps
- **Timer** — 1 min to 99 h 59 min
- **Data** — RS232 remote control

SECTION III

Specifications

Technical data — DMS7

Specifications	
Brand	ALab™ by ACS Material
Model	DMS7
ACS Cat. No.	Parent ALDMS70F; ALDMS700
Product type	LCD digital magnetic stirrer with 7-inch glass-ceramic plate (no heating)
Work plate dimension	184 × 184 mm (7 inch)
Work plate material	Glass ceramic
Motor type	Brushless DC motor
Stirring positions	1
Maximum stirring volume [H_2O]	20 L
Maximum stirrer bar length	80 mm
Speed range	50 to 1500 rpm, increment 1 rpm
Speed display	LCD
Data connector	RS232
Protection class	IP21
Timer function	1 min to 99 h 59 min
Motor output power	10 W
Power	50 W
Voltage, frequency	100 to 240 V, 50/60 Hz
Dimensions [L × W × H]	360 × 230 × 110 mm
Weight	4.3 kg
Permissible ambient temperature and humidity	5 to 40°C, 80% RH

Control and safety

Function	Detail
Timer	1 min to 99 h 59 min; the buzzer sounds at the end of the countdown
Safety lock	Locks the settings against accidental changes during operation
Buzzer	Sounds when the unit detects a fault and when the timer countdown ends
RS232 data connector	Remote control from a PC

SECTION IV

Applications

Magnetic stirring of up to 20 L of water on a 7-inch plate in the laboratory, without heating.

Specifications are per the tables above.

Revision Date: 10/23/2026

DISCLAIMER

ALab™ is a trademark of ACS Material, LLC. ACS Material, LLC believes that the information in this Technical Data Sheet is accurate and represents the best and most current information available to us. ACS Material makes no representations or warranties, either express or implied, regarding the suitability of the equipment for any application or the accuracy of the information contained within this document. Specifications are typical and may vary by model; assess product details and application suitability for the intended use. Accordingly, ACS Material will not be responsible for damages resulting from use of or reliance upon this information.