TECHNICAL DATA SHEET

ALab™ MS-H280-Pro LED Digital Magnetic Hotplate Stirrer

LED digital magnetic hotplate stirrer · Ø135 mm plate · RT to 280°C · 200 to 1500 rpm · 3 L · not for chemical fields



ALab™ MS-H280-Pro LED Digital Magnetic Hotplate Stirrer

The ALab™ MS-H280-Pro LED Digital Magnetic Hotplate Stirrer; image shown for reference.

CONTENTS

01 Product Overview
02 Core Advantages
03 Specifications
04 Applications

ACS MATERIAL, LLC

959 E Walnut St., Suite 100
Pasadena, CA 91106, USA

Phone +1 (866) 227-0656
Fax +1 (781) 518-0284

contact@acsmaterial.com

Revision Date **10/23/2026**

SECTION I

Product Overview

NOT FOR USE IN THE CHEMICAL FIELD. The MS-H280-Pro is not available for chemical fields. Consult ACS Material to identify a suitable model for your specific application.

The ALab™ MS-H280-Pro is a compact LED digital magnetic hotplate stirrer for small-volume tasks and daily applications. It stirs up to 3 L of water at 200 to 1500 rpm and heats the 5-inch (Ø135 mm) plate from RT to 280°C. The LED display shows temperature and speed; a PT1000 sensor controls the liquid temperature; 320°C overheating protection and a "HOT" warning above 50°C are built in.

SECTION II

Core Advantages

- **Size** — 150 × 260 mm, 1.8 kg
- **Speed** — 200 to 1500 rpm
- **Control** — PT1000 external sensor
- **Heating** — RT to 280°C
- **Display** — LED temperature and speed
- **Use** — not for chemical fields

SECTION III

Specifications

Technical data — MS-H280-Pro

Specifications	
Brand	ALab™ by ACS Material
Model	MS-H280-Pro
ACS Cat. No.	Parent ALMSHO0F; ALMSHO00
Product type	LED digital magnetic hotplate stirrer with 5-inch plate
Work plate dimension	Ø135 mm (5 inch)
Motor type	Brushless DC motor
Stirring positions	1
Maximum stirring volume [H_2O]	3 L
Maximum stirrer bar length	50 mm
Speed range	200 to 1500 rpm
Speed display	LED
Temperature display	LED
Heating temperature range	RT to 280°C
Temperature control accuracy (liquid)	±1°C (<100°C), ±1% (>100°C)
Overheating protection	320°C
Temperature display accuracy	±1°C
External temperature sensor	PT1000
"HOT" warning	50°C
Motor rating output	3 W
Power	515 W
Heating output	500 W
Voltage, frequency	100 to 120 V / 200 to 240 V, 50/60 Hz
Footprint [W × D]	150 × 260 mm
Weight	1.8 kg
Permissible ambient temperature and humidity	5 to 40°C, 80% RH

Specifications	
Use restriction	Not available for chemical fields

Control and safety

Function	Detail
Use restriction	Not available for chemical fields
Overheating protection	320℃
"HOT" warning	Flashes "HOT" when the work plate temperature is above 50℃, even when the hotplate is turned off
External temperature control	PT1000 temperature sensor for control of the liquid temperature

SECTION IV

Applications

Small-volume heating and magnetic stirring of up to 3 L of water and daily applications outside the chemical field, from RT to 280℃.

Not available for chemical fields. Specifications are per the tables above.

Revision Date: 10/23/2026

DISCLAIMER

ALab™ is a trademark of ACS Material, LLC. ACS Material, LLC believes that the information in this Technical Data Sheet is accurate and represents the best and most current information available to us. ACS Material makes no representations or warranties, either express or implied, regarding the suitability of the equipment for any application or the accuracy of the information contained within this document. Specifications are typical and may vary by model; assess product details and application suitability for the intended use. Accordingly, ACS Material will not be responsible for damages resulting from use of or reliance upon this information.