TECHNICAL DATA SHEET

ALab™ MS-H380-Pro LCD Digital Magnetic Hotplate Stirrer

LCD digital magnetic hotplate stirrer · 140 × 140 mm plate · RT to 380°C · 200 to 1500 rpm · 5 L · usable in chemical laboratories



ALab™ MS-H380-Pro LCD Digital Magnetic Hotplate Stirrer

The ALab™ MS-H380-Pro LCD Digital Magnetic Hotplate Stirrer; image shown for reference.

CONTENTS

01 Product Overview

02 Core Advantages

03 Specifications

04 Applications

ACS MATERIAL, LLC

959 E Walnut St., Suite 100

Pasadena, CA 91106, USA

Phone +1 (866) 227-0656

Fax +1 (781) 518-0284

contact@acsmaterial.com

Revision Date **10/23/2026**

SECTION I

Product Overview

CHEMICAL LABORATORIES. The MS-H380-Pro can be used in chemical laboratories and is resistant to chemical corrosion. Follow your laboratory's safety procedures when heating chemicals.

The ALab™ MS-H380-Pro is an LCD digital magnetic hotplate stirrer with a square 140 × 140 mm aluminum plate with ceramic coating for immediate heat transfer, heating from RT to 380°C. It stirs up to 5 L of water at 200 to 1500 rpm. The high-resolution LCD shows actual temperature and speed; external temperature control is possible with a PT1000 sensor (±0.2°C); 420°C overheating protection is built in.

SECTION II

Core Advantages

- **Heating** — RT to 380°C
- **Speed** — 200 to 1500 rpm
- **Control** — PT1000 control, ±0.2°C
- **Plate** — 140 × 140 mm, ceramic coated
- **Display** — LCD, ±0.1°C
- **Use — chemical laboratories**

SECTION III

Specifications

Technical data — MS-H380-Pro

Specifications	
Brand	ALab™ by ACS Material
Model	MS-H380-Pro
ACS Cat. No.	Parent ALMH380F; ALMH380P
Product type	LCD digital magnetic hotplate stirrer with 140 × 140 mm ceramic-coated plate
Work plate dimension [W × D]	140 × 140 mm
Work plate material	Aluminum cover with ceramic coating
Motor type	Brushless DC motor
Stirring positions	1
Maximum stirring volume [H_2O]	5 L
Maximum stirrer bar length	50 mm
Speed range	200 to 1500 rpm
Speed display	LCD
Temperature display	LCD
Heating temperature range	RT to 380°C
Temperature control accuracy (liquid)	±1°C (<100°C), ±1% (>100°C)
Overheating protection	420°C
Temperature display accuracy	±0.1°C
External temperature sensor	PT1000 (accuracy ±0.2°C)
Protection class	IP21
Power	510 W
Heating output	500 W
Voltage, frequency	100 to 120 V / 200 to 240 V, 50/60 Hz
Dimensions [W × D × H]	320 × 180 × 108 mm
Weight	2.2 kg
Permissible ambient temperature and humidity	5 to 40°C, 80% RH

Specifications	
Chemical use	Can be used in chemical laboratories; resistant to chemical corrosion

Control and safety

Function	Detail
Chemical use	Can be used in chemical laboratories; resistant to chemical corrosion
Overheating protection	420℃
External temperature control	PT1000 temperature sensor, accuracy ±0.2℃, for control of the liquid temperature

SECTION IV

Applications

Heating to 380℃ and magnetic stirring of up to 5 L of water in laboratory work, including chemical laboratories.

Can be used in chemical laboratories. Specifications are per the tables above.

Revision Date: 10/23/2026

DISCLAIMER

ALab™ is a trademark of ACS Material, LLC. ACS Material, LLC believes that the information in this Technical Data Sheet is accurate and represents the best and most current information available to us. ACS Material makes no representations or warranties, either express or implied, regarding the suitability of the equipment for any application or the accuracy of the information contained within this document. Specifications are typical and may vary by model; assess product details and application suitability for the intended use. Accordingly, ACS Material will not be responsible for damages resulting from use of or reliance upon this information.