TECHNICAL DATA SHEET

ALab™ MS-M-S10 10-Position Magnetic Stirrer

10-position magnetic stirrer · 180 × 450 mm plate · 0 to 1100 rpm · 0.4 L per position



ALab™ MS-M-S10 10-Position Magnetic Stirrer

The ALab™ MS-M-S10 10-Position Magnetic Stirrer; image shown for reference.

CONTENTS

01 Product Overview

02 Core Advantages

03 Specifications

04 Applications

ACS MATERIAL, LLC

959 E Walnut St., Suite 100

Pasadena, CA 91106, USA

Phone +1 (866) 227-0656

Fax +1 (781) 518-0284

contact@acsmaterial.com

Revision Date **10/23/2026**

SECTION I

Product Overview

The ALab™ MS-M-S10 is a 10-position magnetic stirrer without heating, with a 180 × 450 mm work plate. It stirs up to 0.4 L of water at each of 10 positions at 0 to 1100 rpm, set on a scale.

A maintenance-free brushless DC motor (motor output power 4 W, power 20 W) drives the stirring; the space-saving design maximizes the use of bench space.

SECTION II

Core Advantages

- **Positions** — 10 × 0.4 L
- **Motor** — brushless DC, 4 W
- **Power** — 20 W
- **Speed** — 0 to 1100 rpm
- **Control** — knob with scale

SECTION III

Specifications

Technical data — MS-M-S10

Specifications	
Brand	ALab™ by ACS Material
Model	MS-M-S10
ACS Cat. No.	Parent ALMSM00F; ALMSM000
Product type	10-position magnetic stirrer
Work plate dimension [W × D]	180 × 450 mm
Motor type	Brushless DC motor
Stirring positions	10
Maximum stirring quantity [H_2O]	0.4 L × 10
Maximum stirrer bar length	40 mm
Speed range	0 to 1100 rpm
Speed display	Scale
Protection class	IP20
Motor output power	4 W
Power	20 W
Voltage, frequency	100 to 120 V / 200 to 240 V, 50/60 Hz
Published dimensions	182 × 622 × 65 mm
Weight	3.2 kg
Permissible ambient temperature and humidity	5 to 40°C, 80% RH

Control and design

Function	Detail
Speed setting	Knob with scale, 0 to 1100 rpm
Motor	Brushless DC motor, maintenance free
Positions	10 stirring positions on one work plate
Protection class	IP20

SECTION IV

Applications

The MS-M-S10 provides ten stirring positions without heating for parallel stirring of small volumes.

Parallel stirring of up to 10 small samples. Specifications are per the tables above.

Revision Date: 10/23/2026

DISCLAIMER

ALab™ is a trademark of ACS Material, LLC. ACS Material, LLC believes that the information in this Technical Data Sheet is accurate and represents the best and most current information available to us. ACS Material makes no representations or warranties, either express or implied, regarding the suitability of the equipment for any application or the accuracy of the information contained within this document. Specifications are typical and may vary by model; assess product details and application suitability for the intended use. Accordingly, ACS Material will not be responsible for damages resulting from use of or reliance upon this information.