TECHNICAL DATA SHEET

ALab™ MS7-H380-E LCD Digital Magnetic Hotplate Stirrer

LCD digital magnetic hotplate stirrer · 184 × 184 mm ceramic-coated plate · RT to 380°C · 80 to 1500 rpm · 20 L



ALab™ MS7-H380-E LCD Digital Magnetic Hotplate Stirrer

The ALab™ MS7-H380-E LCD Digital Magnetic Hotplate Stirrer; image shown for reference.

CONTENTS

01 Product Overview

02 Core Advantages

03 Specifications

04 Applications

ACS MATERIAL, LLC

959 E Walnut St., Suite 100

Pasadena, CA 91106, USA

Phone +1 (866) 227-0656

Fax +1 (781) 518-0284

contact@acsmaterial.com

Revision Date **10/23/2026**

SECTION I

Product Overview

The ALab™ MS7-H380-E is an LCD digital magnetic hotplate stirrer with a 7-inch (184 × 184 mm) aluminum plate with ceramic coating. It heats from RT to 380°C in 1°C increments and stirs up to 20 L of water at 80 to 1500 rpm.

A diversion platform and slope keep liquids out of the unit. External PT1000 control (±0.2°C), dry-burn, overcurrent, ground-fault and overtemperature protection, 410°C overheating protection and a "HOT" warning above 50°C are built in.

SECTION II

Core Advantages

- **Plate** — 7-inch, ceramic coated
- **Stirring** — 80 to 1500 rpm, 20 L
- **Safety** — 410°C, HOT warning
- **Heating** — RT to 380°C
- **Control** — PT1000, ±0.2°C
- **Design** — Spill diversion

SECTION III

Specifications

Technical data — MS7-H380-E

Specifications	
Brand	ALab™ by ACS Material
Model	MS7-H380-E
ACS Cat. No.	Parent ALMS7E0F; ALMS7E00
Product type	LCD digital magnetic hotplate stirrer with 7-inch ceramic-coated plate
Work plate dimension	184 × 184 mm (7 inch)
Work plate material	Aluminum cover with ceramic coating
Motor type	DC brush motor
Stirring positions	1
Maximum stirring volume [H_2O]	20 L
Maximum stirrer bar size	80 × 10 mm
Speed range	80 to 1500 rpm
Speed display	LCD, resolution 1 rpm
Temperature display	LCD
Heating temperature range	RT to 380°C, increment 1°C
Temperature control accuracy (liquid)	±1°C (<100°C), ±1% (>100°C)
Overheating protection	410°C
External temperature sensor	PT1000 (accuracy ±0.2°C)
"HOT" warning	50°C
Protection class	IP21
Power	900 W
Voltage, frequency	100 to 120 V, 60 Hz / 200 to 240 V, 50 Hz
Dimensions [W × D × H]	366 × 240 × 126 mm
Weight	3.5 kg
Permissible ambient temperature and humidity	5 to 40°C, 80% RH

Control and safety

Function	Detail
Protection functions	Dry-burn, overcurrent, ground-fault and overtemperature protection
Overheating protection	Overheating protection at 410°C
External temperature control	PT1000 temperature sensor, accuracy ±0.2°C, for control of the sample temperature
"HOT" warning	"HOT" flashes on the display when the plate surface is above 50°C, even after the power is switched off
Spill protection	Diversion platform and slope prevent liquids from entering the unit

SECTION IV

Applications

Heating from RT to 380°C and magnetic stirring of up to 20 L of water on a 7-inch plate in the laboratory.

Specifications are per the tables above.

Revision Date: 10/23/2026

DISCLAIMER

ALab™ is a trademark of ACS Material, LLC. ACS Material, LLC believes that the information in this Technical Data Sheet is accurate and represents the best and most current information available to us. ACS Material makes no representations or warranties, either express or implied, regarding the suitability of the equipment for any application or the accuracy of the information contained within this document. Specifications are typical and may vary by model; assess product details and application suitability for the intended use. Accordingly, ACS Material will not be responsible for damages resulting from use of or reliance upon this information.