TECHNICAL DATA SHEET

Levon™ DP100-BE Dip Coater

0.1–600 mm/min · 0–100 mm lift stroke · ±0.01 mm displacement accuracy · 100 stored recipes



Levon™ DP100-BE Dip Coater — Representative Configuration

The Levon™ DP100-BE Dip Coater is a compact benchtop dip coater with a 4.3-inch full-color touchscreen and manual vertical height adjustment. Image shown for reference; final configuration is confirmed in the quotation.

CONTENTS

01 Product Overview

02 Core Advantages

03 Specifications

04 Applications

ACS MATERIAL, LLC

959 E Walnut St., Suite 100

Pasadena, CA 91106, USA

Phone +1 (866) 227-0656

Fax +1 (781) 518-0284

contact@acsmaterial.com

Revision Date **10/21/2026**

SECTION I

Product Overview

Levon™ DP100-BE Dip Coater is a benchtop dip coater with a running speed of 0.1–600 mm/min, a 0–100 mm lift stroke, ±0.01 mm displacement accuracy and storage for 100 named coating recipes.

The DP100-BE is operated from a 4.3-inch full-color touchscreen with a built-in help function and operating instructions. Its compact structure is designed for placement in a glovebox, and manual vertical height adjustment allows flexible positioning. The rated linear thrust is >50 N; immersion time and repeat coating interval time are each settable from 1 to 9,999.9 s, with 1 to 999 repeat coating cycles. Substrates up to 100 × 100 × 5 mm are supported; the unit measures 227 × 350 × 416 mm (W × D × H).

SECTION II

Core Advantages

— **4.3-inch touchscreen** 4.3-inch full-color touchscreen operation.

— **Built-in help** Built-in help function and operating instructions.

— **100 stored recipes** 100 coating recipes can be named and stored.

— **Compact structure for gloveboxes** Compact structure for placement in a glovebox; 227 × 350 × 416 mm (W × D × H).

— **Manual height adjustment** Manual vertical height adjustment for flexible positioning.

— **Repeat coating** 1 to 999 repeat coating cycles with a repeat coating interval time of 1–9,999.9 s.

SECTION III

Specifications

Technical data — DP100-BE

Specifications	
Parameter	**Specification**
Brand	Levon™ by ACS Material
Product Name	Levon™ DP100-BE Dip Coater
Model	DP100-BE
SKU #	LVDP10BE
Product type	Dip coater
Running speed	0.1–600 mm/min
Lift stroke	0–100 mm (other strokes can be customized)
Displacement accuracy	±0.01 mm
Rated linear thrust	>50 N
Immersion time	1–9,999.9 s
Repeat coating interval time	1–9,999.9 s
Repeat coating cycles	1 to 999
Substrate size (wafer)	≤100 × 100 × 5 mm
Coating recipes	100 recipes can be named and stored
Display	4.3-inch full-color touchscreen
Operating aids	Built-in help function and operating instructions
Height adjustment	Manual vertical height adjustment
Dimensions [W × D × H]	227 × 350 × 416 mm
Packing	Carton packaging
Warranty	1-year product warranty

Scope of delivery

— **Standard configuration:** one DP100-BE main unit, carton packaging.

— **Lift stroke** — 0–100 mm; other strokes can be customized (confirm when ordering).

SECTION IV

Applications

For dip coating of substrates up to 100 × 100 × 5 mm at running speeds of 0.1–600 mm/min with a 0–100 mm lift stroke, including glovebox setups. The DP100-BE is designed for compact semiconductor research.

Product value: programmable dip coating at 0.1–600 mm/min with ±0.01 mm displacement accuracy, 1 to 999 repeat coating cycles and a compact design for placement in a glovebox.

Revision Date: 10/21/2026

DISCLAIMER

Levon™ is a trademark of ACS Material, LLC. ACS Material, LLC believes that the information in this Technical Data Sheet is accurate and represents the best and most current information available to us. ACS Material makes no representations or warranties, either express or implied, regarding the suitability of the equipment for any application or the accuracy of the information contained within this document. Specifications are typical and may vary; confirm product details and application suitability at the time of quotation. Accordingly, ACS Material will not be responsible for damages resulting from use of or reliance upon this information.