



ACS Material Equipment Series

Extrova™ Plate Press Machine

- | | |
|------|------------------------|
| I. | Product Overview |
| II. | Product Features |
| III. | Product Specifications |

Contact Information:

ACS Material, LLC
Address: 959 E Walnut St., Suite 100
Pasadena, CA 91106, USA
Phone: (866) 227-0656
Fax: (781) 518-0284
E-Mail: contact@acsmaterial.com

I. Product Overview

1) Main Unit



Photo of Extrova™ Plate Press Machine

II. Product Features

The Extrova™ Plate Press Machine is a versatile hot and cold press machine designed for precision temperature control and efficient operation. With an adjustable capacity ranging from 3 to 30 tons, it offers a temperature range from room temperature to 350°C, controlled by a precision PLC module. The machine features a high-performance hydraulic system that ensures smooth operation with automatic pressure compensation, making it ideal for various industrial applications. Its robust design includes high-temperature-resistant plates and efficient cooling systems, providing both reliability and ease of maintenance..

III. Product Specifications

Product Name	Extrova™ Plate Press Machine
SKU	ERPPM001
Dimensions (d x w x h)	1060 × 470 × 1200 mm
Weight	Approx. 690kg (equipped with casters for easy movement)

Power Supply	3-phase, AC380V, 25A
Weight	Approx. 690kg (equipped with casters for easy movement)
Capacity	Adjustable from 3 to 30T
Temperature Range	Room Temp. to 350 °C
Temperature Controller	Precision module with PLC control
Timer	LED display, time range 0.1s – 99min – 9.9hr
Temperature Control Method	P.I.D microcomputer control, ensuring stable performance and precise temperature regulation
Heater	Built-in cylindrical heating mold (scientifically designed hole positions, fast heating, long lifespan, easy maintenance)
Heating Time	Approx. 15min from room temperature to 170°C
Hot Press Plate	500×500mm high-temperature-resistant imported SKD steel plate, carbonized and quenched surface for fast heat conduction, parallel pressure without deformation, internal tap water cooling
Cold Press Plate	300×300mm, internally cooled by tap water
Hot Plate Pressure	16MPa
Cold Plate Pressure	16MPa
Hydraulic System	Closed-loop hydraulic flow control system (GPY oil pump drives high-performance electro-hydraulic system with high-precision, resistance-free piston for consistent speed control, featuring automatic pressure compensation; primary and secondary pressurization times can be preset, strong load capacity, smooth operation; automatic pressurization, pressure holding, and pressure release)
Oil Cylinder Stroke	Max 180 mm
Oil Cylinder Speed	11mm/s
Pressure Gauge	0–210kg/sq.cm

Disclaimer: ACS Material, LLC believes that the information in this Technical Data Sheet is accurate and represents the best and most current information available to us. ACS Material makes no representations or warranties either express or implied, regarding the suitability of the material for any purpose or the accuracy of the information contained within this document. Accordingly, ACS Material will not be responsible for damages resulting from use of or reliance upon this information.