

TECHNICAL DATA SHEET

ALab™ Pocket Testers

Pocket pH, ORP, conductivity and pH/conductivity testers · eight models · standard and Bluetooth



ALab™ Pocket Testers

The ALab™ Pocket Testers (left to right: DPH1, DPH1+, DORP1, DORP1+).

CONTENTS

- 01 Product Overview
- 02 Core Advantages
- 03 Specifications
- 04 Applications

ACS MATERIAL, LLC

959 E Walnut St., Suite 100
Pasadena, CA 91106, USA
Phone +1 (866) 227-0656
Fax +1 (781) 518-0284
contact@acsmaterial.com
Revision Date **10/16/2026**

SECTION I

Product Overview

The ALab™ Pocket Testers offer eight pocket testers for pH, ORP, conductivity and pH/conductivity, in a standard series and a Bluetooth series with mobile APP.

All models have replaceable probes, a multi-color backlight display, automatic data locking, 4×1.5V AAA batteries and protection class IP67.

SECTION II

Core Advantages

- **Probes** — replaceable
- **Series** — standard, Bluetooth
- **Power** — 4×AAA
- **Display** — multi-color backlight
- **Models** — eight
- **Protection** — IP67

SECTION III

Specifications

Technical data — eight pocket testers

Specifications	
Brand	ALab™ by ACS Material
Model	DPH1, DPH1+, DORP1, DORP1+, DEC1, DEC1+, DPC1, DPC1+
SKU #	ALECPK00
Product Type	Pocket pH / ORP / conductivity / pH-conductivity testers (standard and Bluetooth)
Power supply	4×1.5V AAA alkaline batteries, pre-installed
Protection class	IP67

Models, specifications and included items — eight pocket testers

Parameters and probes of each model								
Parameter / probe	DPH1	DPH1+	DORP1	DORP1+	DEC1	DEC1+	DPC1	DPC1+
pH, mV, °C	Yes	Yes	—	—	—	—	Yes	Yes
mV (ORP), °C	Yes	Yes	Yes	Yes	—	—	Yes	Yes
Cond., TDS, Sal., Res., °C	—	—	—	—	Yes	Yes	Yes	Yes
Default probe PH1-S	Yes	Yes	—	—	—	—	—	—
Default probe ORP1-S	—	—	Yes	Yes	—	—	—	—
Default probe EC1-S	—	—	—	—	Yes	Yes	—	—
Default probe PC1-S	—	—	—	—	—	—	Yes	Yes
Optional probe PH1-S	—	—	—	—	—	—	Yes	Yes
Optional probe ORP1-S	Yes	Yes	—	—	—	—	Yes	Yes
Optional probe EC1-S	—	—	—	—	—	—	Yes	Yes

Specifications — standard models (DPH1, DORP1, DEC1, DPC1)		
Parameter	Specification	Applies to
pH: Measurement range	(-2.00~16.00)pH	DPH1, DPC1
pH: Resolution	0.1/0.01	DPH1, DPC1
pH: Accuracy	±0.01pH ±one digit	DPH1, DPC1
pH: Calibration points	1, 2, -3pts automatic	DPH1, DPC1
pH: ATC range	0~60°C(32~140°F)	DPH1, DPC1
ORP: Measurement range	(-1000.0~+1000.0)mV	DPH1, DORP1, DPC1
ORP: Resolution	0.1/1	DPH1, DORP1, DPC1
ORP: Accuracy	±0.1%F.S ±one digit	DPH1, DORP1, DPC1
Conductivity: Measurement range	0~19.99mS/cm, Auto-ranging: 0~19.99μS/cm; 20.0~199.9μS/cm; 200~1999μS/cm; 2.00~19.99mS/cm. TDS: 0.0mg/L~10.0g/L (TDS factor adjustable). Resistivity: 50Ω-cm~20MΩ-cm. Salinity: 0~10ppt	DEC1, DPC1
Conductivity: Resolution	0.01/0.1/1	DEC1, DPC1
Conductivity: Accuracy	±1.0%F.S ±one digit	DEC1, DPC1
Temperature: Measurement range	0~60°C(32~140°F)	All standard models
Temperature: Accuracy	±0.2°C	All standard models

Specifications — Bluetooth models (DPH1+, DORP1+, DEC1+, DPC1+)								
Parameter	Specification	Applies to						
pH: Measurement range	(-2.00~16.00)pH	DPH1+, DPC1+						
pH: Resolution	0.1/0.01	DPH1+, DPC1+						
pH: Accuracy	±0.01pH ±one digit	DPH1+, DPC1+						
pH: Calibration points	1, 2, -3pts automatic	DPH1+, DPC1+						
pH: ATC range	0~60°C(32~140°F)	DPH1+, DPC1+						
ORP: Measurement range	(-1000.0~+1000.0)mV	DPH1+, DORP1+, DPC1+						
ORP: Resolution	0.1/1	DPH1+, DORP1+, DPC1+						
ORP: Accuracy	±0.1%F.S ±one digit	DPH1+, DORP1+, DPC1+						
Conductivity: Measurement range	0~19.99mS/cm, Auto-ranging: 0~19.99µS/cm; 20.0~199.9µS/cm; 200~1999µS/cm; 2.00~19.99mS/cm. TDS: 0.0mg/L~10.0g/L (TDS factor adjustable). Resistivity: 50Ω-cm~20MΩ-cm. Salinity: 0~10ppt	DEC1+, DPC1+						
Conductivity: Resolution	0.01/0.1/1	DEC1+, DPC1+						
Conductivity: Accuracy	±1.0%F.S ±one digit	DEC1+, DPC1+						
Temperature: Measurement range	0~60°C(32~140°F)	All Bluetooth models						
Temperature: Accuracy	±0.2°C	All Bluetooth models						
APP: Calibration reminder	Yes	All Bluetooth models						
APP: Sample ID Classification	Yes	All Bluetooth models						
APP: Timing datalogging	Yes	All Bluetooth models						
APP: Operation guider	Yes	All Bluetooth models						
APP: Various display modes	Yes	All Bluetooth models						
Test kit — included items by model								
Item	DPH1	DPH1+	DORP1	DORP1+	DEC1	DEC1+	DPC1	DPC1+
Tester	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Probe PH1-S, pre-installed	Yes	Yes	–	–	–	–	–	–
Probe ORP1-S, pre-installed	–	–	Yes	Yes	–	–	–	–
Probe EC1-S, pre-installed	–	–	–	–	Yes	Yes	–	–
Probe PC1-S, pre-installed	–	–	–	–	–	–	Yes	Yes
pH buffer solution: pH4.00/7.00/10.01, 30mL, one for each	Yes	Yes	–	–	–	–	–	–
3.0 mol KCl pH/ORP soaking solution: 10mL, 1 bottle	Yes	Yes	Yes	Yes	–	–	Yes	Yes
Sample vials: 30mL (quantity)	3	3	1	1	2	2	4	4
Standard ORP solution: 222mV, 30mL	–	–	Yes	Yes	–	–	–	–
Standard Cond solution: 1413µS/12.88mS/cm, 30mL, one for each	–	–	–	–	Yes	Yes	Yes	Yes
pH buffer solution: pH4.00/7.00, 30mL, one for each	–	–	–	–	–	–	Yes	Yes
4x1.5V AAA alkaline batteries (pre-installed)	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Lanyard	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Hard carrying case (L/W/H: 28.0×23.0×8.2cm)	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes

Scope of delivery

- **Standard configuration:** one ALab™ pocket tester of the selected model with the items marked for that model in the Included items table.
- **Optional:** optional probes as listed in the first table. Specify further items separately in the quotation.

SECTION IV

Applications

Suited to portable measurement of pH, ORP, conductivity, TDS, salinity and resistivity; the Bluetooth models add a mobile APP with datalogging.

Select the model before ordering.

Revision Date: 10/16/2026

DISCLAIMER

ALab™ is a trademark of ACS Material, LLC. ACS Material, LLC believes that the information in this Technical Data Sheet is accurate and represents the best and most current information available to us. ACS Material makes no representations or warranties, either express or implied, regarding the suitability of the equipment for any application or the accuracy of the information contained within this document. Specifications are typical and may vary; confirm product details and application suitability at the time of quotation. Accordingly, ACS Material will not be responsible for damages resulting from use of or reliance upon this information.