

TECHNICAL DATA SHEET

ALab™ Portable Meters

Portable pH, ORP, conductivity and dissolved oxygen meters · eight models · 3.5-inch TFT color display



ALab™ Portable Meters

Portable Meters series illustration. This document covers only the models listed in the specification and model tables. Individual units in the illustration are not identified by model number.

CONTENTS

- 01 Product Overview
- 02 Core Advantages
- 03 Specifications
- 04 Applications

ACS MATERIAL, LLC

959 E Walnut St., Suite 100
Pasadena, CA 91106, USA

Phone +1 (866) 227-0656

Fax +1 (781) 518-0284

contact@acsmaterial.com

Revision Date 10/16/2026

SECTION I

Product Overview

The ALab™ Portable Meters offer eight portable meters for pH, ORP, conductivity and dissolved oxygen with a 3.5-inch TFT color display and a new UI interface.

All models store up to 3000 groups of data, have an auto. timing datalogger, a rechargeable lithium battery with Type-C charging and protection class IP57.

SECTION II

Core Advantages

- **Display** — 3.5-inch TFT color
- **Storage** — 3000 groups
- **Power** — Li battery, Type-C
- **Interface** — new UI
- **Models** — eight
- **Protection** — IP57

SECTION III

Specifications

Technical data — eight portable meters

Specifications	
Brand	ALab™ by ACS Material
Model	DPH10, DORP10, DEC10, DDO10, DPC10, DPD10, DCD10, DPO10
SKU #	ALECPR00
Product Type	Portable pH / ORP / conductivity / dissolved oxygen meters
Display	3.5-inch TFT color display
Data storage	Up to 3000 groups
Power supply	Rechargeable lithium battery; Type-C charging socket
Protection class	IP57

Models, specifications and included items — eight portable meters

Parameters measured by each model								
Parameter	DPH10	DORP10	DEC10	DDO10	DPC10	DPD10	DCD10	DPO10
pH, mV, °C	Yes	–	–	–	Yes	Yes	–	Yes
mV (ORP), °C	Yes	Yes	–	–	Yes	Yes	–	Yes
Cond., TDS, Sal., Res., °C	–	–	Yes	–	Yes	–	Yes	–
DO, °C	–	–	–	Yes	–	Yes	Yes	–

Specifications — Portable Meters		
Parameter	Specification	Applies to
pH: Measurement range	(-2.000~20.000)pH	DPH10, DPC10, DPD10, DPO10
pH: Resolution	0.1/0.01/0.001	DPH10, DPC10, DPD10, DPO10
pH: Accuracy	±0.002pH ±one digit	DPH10, DPC10, DPD10, DPO10
pH: Calibration points	1, 2, -3pts automatic	DPH10, DPC10, DPD10, DPO10
pH: ATC range	(0.0~100.0)°C/(32.0~212.0)°F	DPH10, DPC10, DPD10, DPO10
ORP: Measurement range	(-1999.9~+1999.9)mV	DPH10, DORP10, DPC10, DPD10, DPO10
ORP: Resolution	0.1/1	DPH10, DORP10, DPC10, DPD10, DPO10
ORP: Accuracy	±0.03%F.S ±one digit	DPH10, DORP10, DPC10, DPD10, DPO10
Conductivity: Measurement range	0~2000.0mS/cm, Auto-ranging: 0~19.999µS/cm; 20.0~199.9µS/cm; 200~1999µS/cm; 2.00~19.99mS/cm; 20.00~199.9mS/cm; 200.0~2000mS/cm (K=10). Match test range: 0~200mS/cm. TDS: 0~100.0g/L (TDS factor adjustable). Resistivity: 5.000Ω-cm~100.0MΩ-cm. Salinity: 0~100ppt	DEC10, DPC10, DCD10
Conductivity: Calibration points	one point	DEC10, DPC10, DCD10
Conductivity: Resolution	0.001/0.01/0.1/1	DEC10, DPC10, DCD10
Conductivity: ATC range	(0.0~50.0)°C/(32.0~122.0)°F	DEC10, DPC10, DCD10
Conductivity: Accuracy	±0.5%F.S ±one digit	DEC10, DPC10, DCD10
DO: Measurement range	(0.00~20.00)mg/L	DDO10, DPD10, DCD10
DO: Accuracy	±0.30mg/L	DDO10, DPD10, DCD10
DO: DO saturation	(0.0~200.0)%	DDO10, DPD10, DCD10

Specifications — Portable Meters (continued)								
Parameter	Specification	Applies to						
DO: Automatic barometric pressure compensation	(0~200.0)kPa	DDO10, DPD10, DCD10						
DO: Automatic temperature compensation	(0.0~50.0)°C/(32.0~122.0)°F	DDO10, DPD10, DCD10						
DO: Manual salinity compensation	0~45ppt	DDO10, DPD10, DCD10						
Temperature: Measurement range	(0.0~100.0)°C/(32.0~212.0)°F	All models						
Temperature: Accuracy	±0.2°C	All models						
Others: Charging socket	Type-C	All models						
Others: Power supply	Rechargeable lithium battery	All models						
Others: IP Rating	IP57	All models						

Test kit — included items by model								
Item	DPH10	DORP10	DEC10	DDO10	DPC10	DPD10	DCD10	DPO10
Meter	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Plastic ATC pH probe 201T-H	Yes	–	–	–	Yes	Yes	–	Yes
Plastic ORP probe ORP301	–	Yes	–	–	–	–	–	Yes
Stainless-steel temperature probe TEMP-02H	–	Yes	–	–	–	–	–	Yes
Plastic ATC Cond probe CON201T, K=1.0	–	–	Yes	–	Yes	–	Yes	–
Polarographic DO probe DO01-2M-H, cable length: 2m	–	–	–	Yes	–	Yes	Yes	–
pH buffer solution: pH4.00/7.00/10.01, 50mL, one for each	Yes	–	–	–	Yes	Yes	–	Yes
Standard ORP solution: 222mV, 50mL, 1btl	–	Yes	–	–	–	–	–	Yes
Standard Cond solution: 84µS/1413µS/12.88mS/cm, 50mL, one for each	–	–	Yes	–	Yes	–	Yes	–
Membrane refill solution: DOS-01, 30mL, 1btl	–	–	–	Yes	–	Yes	Yes	–
Membrane sensor caps DOSC: 3pcs/group, 1pkg	–	–	–	Yes	–	Yes	Yes	–
Rechargeable lithium battery (pre-installed)	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Charging cable	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Hard carrying case (L/W/H: 33.0×27.2×8.2cm)	Yes	Yes	Yes	Yes	–	–	–	–
Hard carrying case (L/W/H: 36.0×32.0×9.0cm)	–	–	–	–	Yes	Yes	Yes	Yes

Scope of delivery

- **Standard configuration:** one ALab™ portable meter of the selected model with the items marked for that model in the Included items table.
- **Optional:** none listed. Specify further items separately in the quotation.

SECTION IV

Applications

Suited to portable measurement of pH, ORP, conductivity and dissolved oxygen with a 3.5-inch TFT color display and 3000 stored groups of data.

Select the model before ordering.

Revision Date: 10/16/2026

DISCLAIMER

ALab™ is a trademark of ACS Material, LLC. ACS Material, LLC believes that the information in this Technical Data Sheet is accurate and represents the best and most current information available to us. ACS Material makes no representations or warranties, either express or implied, regarding the suitability of the equipment for any application or the accuracy of the information contained within this document. Specifications are typical and may vary; confirm product details and application suitability at the time of quotation. Accordingly, ACS Material will not be responsible for damages resulting from use of or reliance upon this information.