

TECHNICAL DATA SHEET

ALab™ D1008 Palm Micro Centrifuge

Palm micro centrifuge • 7000 rpm • 2680 ×g • lid-activated • ≤ 45 dB • 0.5 kg



ACS Material ALab™ D1008 Palm Micro Centrifuge

CONTENTS

- 01 Product Overview
- 02 Core Advantages
- 03 Specifications
- 04 Applications

ACS MATERIAL, LLC

959 E Walnut St., Suite 100
Pasadena, CA 91106, USA
Phone +1 (866) 227-0656
Fax +1 (781) 518-0284

contact@acsmaterial.com

Revision Date **08/14/2026**

SECTION I

Product Overview

The ALab™ D1008 Palm Micro Centrifuge is a palm-sized spin-down centrifuge for quick spins, microfiltration of samples, cell separations and other routine laboratory procedures. It reaches 7000 rpm and 2680 ×g, starts on closing the lid and stops on opening it, accelerates and brakes in seconds, and operates at a manufacturer-stated noise level of ≤ 45 dB. A clamp-locking design allows the rotor to be changed without tools. Both rotors and both adapter packs are supplied with the instrument.

SECTION II

Core Advantages

- **2680 ×g from a palm-sized body** — 7000 rpm on both rotors; 160 × 170 × 122 mm, 0.5 kg
- **Lid-activated dual start/stop** — closing the lid starts a brief spin-down; opening it stops the rotor
- **Seconds to speed, seconds to stop** — manufacturer-stated noise level ≤ 45 dB
- **Quick-change rotors** — clamp-locking design, no tools required

SECTION III

Specifications

Technical data

Specifications	
Max. Speed	7000 rpm
Max. RCF	2680 ×g
Rotor Capacity	8 × 0.2 / 0.5 / 1.5 / 2 mL · 32 × 0.2 mL PCR tubes · 4 × 0.2 mL PCR 8-tube strips
Run Time	Continuous operation
Driving Motor	DC motor
Power Requirements	AC 100–240 V, 50/60 Hz · 20 W
Noise Level	≤ 45 dB
Dimensions [D×W×H]	160 × 170 × 122 mm
Weight	0.5 kg

Specifications	
Rotor A8-2P (19201164)	7000 rpm · 2680 ×g · 8 × 0.2/0.5/1.5/2 mL · high-strength plastic
Rotor A4-PCR8P (19201165)	7000 rpm · 2680 ×g · 32 × 0.2 mL PCR tubes, 4 × PCR 8-tube strips
Adapter SA02P2 (19400029)	0.2 mL, for the A8-2P rotor, 8 pcs/pk
Adapter SA05P2 (19400026)	0.5 mL, for the A8-2P rotor, 8 pcs/pk

Maximum RCF applies at the maximum speed of the rotor concerned. $RCF = 1.118 \times 10^{-5} \cdot r[cm] \cdot N^2$; never exceed a rotor's rated speed.

Scope of delivery

- Supplied: D1008 centrifuge, 1 unit
- Supplied: SA02P2 and SA05P2 adapters, 8 pcs each
- Supply: AC 100–240 V, 50/60 Hz
- Supplied: A8-2P and A4-PCR8P rotors, 1 each
- Rotors and adapters are included, not extra
- Cat. Nos. listed for spares and replacements

SECTION IV

Applications

Typical applications for the ALab™ D1008 Palm Micro Centrifuge include:

- **Quick spins** — brief spin-down of tube contents
- **Microfiltration of samples** — as stated by the manufacturer
- **Cell separations** — as stated by the manufacturer
- **Routine laboratory procedures** — handling of 0.2–2 mL tubes and PCR tube / strip formats

Product value: 2680 ×g from a palm-sized, 0.5 kg instrument, with lid-activated operation, seconds-long acceleration and braking, tool-free rotor changes and both rotors plus both adapter packs supplied. Rotor capacity covers 0.2 to 2 mL tubes and PCR 8-tube strips; larger tube formats require a low-speed model.

Revision Date: 08/14/2026

DISCLAIMER

ALab™ is a trademark of ACS Material, LLC. ACS Material, LLC believes that the information in this Technical Data Sheet is accurate and represents the best and most current information available to us. ACS Material makes no representations or warranties, either express or implied, regarding the suitability of the equipment for any application or the accuracy of the information contained within this document. Specifications are typical and may vary; confirm product details and application suitability at the time of quotation. Accordingly, ACS Material will not be responsible for damages resulting from use of or reliance upon this information.