

TECHNICAL DATA SHEET

Levon[™] DP100-BE Dip Coater

Dip coater · 0.1–600 mm/min · 0–100 mm lift stroke · ± 0.01 mm · 100 stored programs · 4.3-inch touch screen



ACS Material Levon[™] DP100-BE Dip Coater

CONTENTS

- 01 Product Overview
- 02 Core Advantages
- 03 Specifications
- 04 Notes

ACS MATERIAL, LLC

959 E Walnut St., Suite 100
Pasadena, CA 91106, USA

Phone +1 (866) 227-0656

Fax +1 (781) 518-0284

contact@acsmaterial.com

Revision Date **09/23/2026**

SECTION I

Product Overview

The Levon™ DP100-BE Dip Coater (SKU LVDP10BE) is a dip coater with a running speed of 0.1–600 mm/min over a 0–100 mm lift stroke (other strokes can be customized), a displacement accuracy of ± 0.01 mm and a rated linear thrust greater than 50 N. Impregnation time and repeat coating interval time are each settable from 1 to 9999.9 s, and a coating can be repeated from 1 to 999 times. Wafers up to $100 \times 100 \times 5$ mm can be selected, and 100 coating programs can be named and stored. It has a 4.3-inch full-color touch screen with a help function and operating instructions, and the manufacturer states that the compact structure can be placed in a glove box.

SECTION II

Core Advantages

- **4.3-inch full-color touch screen** — with help function and operating instructions
- **Programmable repeat coating** — 1 to 999 times; impregnation and interval time 1–9999.9 s each
- **Compact structure** — can be placed in a glove box, as stated by the manufacturer
- **100 stored programs** — coating programs can be named and stored
- **Displacement accuracy ± 0.01 mm** — running speed 0.1–600 mm/min, rated linear thrust >50 N
- **Manual vertical height adjustment** — for flexible positioning

SECTION III

Specifications

Technical data

Specifications	
Running Speed	0.1–600 mm/min
Lift Stroke	0–100 mm (other strokes can be customized)
Displacement Accuracy	± 0.01 mm
Rated Linear Thrust	>50 N
Impregnation Time	1–9999.9 s
Repeat Coating Interval Time	1–9999.9 s
Repeat Coating Times	From 1 time to 999 times
Selectable Size of Wafer	$\leq 100 \times 100 \times 5$ mm
Program Storage	100 coating programs can be named and stored
Display / Operation	4.3-inch full-color touch screen · help function · manual vertical height adjustment

Specifications	
SKU	LVDP10BE
Dimensions [W×D×H]	227 × 350 × 416 mm
Packing	Carton packaging
Warranty	1-year product warranty
Quality Management	ISO 9001 Quality Management System Certification (manufacturer)

Scope of delivery

- Supplied: DP100-BE dip coater, 1 unit
- Packing: carton packaging

SECTION IV**Notes**

Please note the following for the Levon™ DP100-BE Dip Coater:

- **Lift stroke** — 0–100 mm; other strokes can be customized — confirm at quotation
- **Glove box use** — the manufacturer states the compact structure can be placed in a glove box

Product value: a dip coater with 0.1–600 mm/min running speed, ± 0.01 mm displacement accuracy, programmable impregnation time, interval time and repeat count, and 100 named, storable coating programs on a 4.3-inch touch screen, in a 227 × 350 × 416 mm footprint.

Revision Date: 09/23/2026

DISCLAIMER

Levon™ is a trademark of ACS Material, LLC. ACS Material, LLC believes that the information in this Technical Data Sheet is accurate and represents the best and most current information available to us. ACS Material makes no representations or warranties, either express or implied, regarding the suitability of the equipment for any application or the accuracy of the information contained within this document. Specifications are typical and may vary; confirm product details and application suitability at the time of quotation. Accordingly, ACS Material will not be responsible for damages resulting from use of or reliance upon this information.