

TECHNICAL DATA SHEET

ALab™ SP-XUV5101 Touch Screen Xenon Lamp Double Beam UV-Vis Spectrophotometer

Touch screen xenon lamp double beam UV Vis spectrophotometer • 190–1100 nm • 1.0nm bandwidth



ALab™ SP-XUV5101 Touch Screen Xenon Lamp Double Beam UV-Vis Spectrophotometer

The ALab™ SP-XUV5101 spectrophotometer. Image shown for reference.

CONTENTS

- 01 Product Overview
- 02 Core Advantages
- 03 Specifications
- 04 Applications

ACS MATERIAL, LLC

959 E Walnut St., Suite 100
Pasadena, CA 91106, USA

Phone +1 (866) 227-0656

Fax +1 (781) 518-0284

contact@acsmaterial.com

Revision Date **10/17/2026**

SECTION I

Product Overview

The ALab™ SP-XUV5101 is a touch screen xenon lamp double beam UV Vis spectrophotometer with a 10.1 inches high resolution TFT colored capacitive touch screen (1024*600) and a windows graphic interface, offering photometric measurement, quantitative measurement, kinetics, spectrum scan, DNA\Protein test and multi-wavelength test.

Wavelength range 190–1100 nm with 1.0nm spectral bandwidth; light source: Hamamatsu Xenon Lamp (Japan). Test data and working curves are saved in the in-house memory (up to 1024M) and exported through the USB port.

SECTION II

Core Advantages

- **Touch screen** — 10.1-inch, 1024×600
- **Optics** — double beam
- **Functions** — photometric, scan, kinetics
- **Range** — 190–1100 nm, 1.0nm
- **Light source** — xenon lamp
- **Data** — 1024M memory, USB

SECTION III

Specifications

Technical data — SP-XUV5101

Specifications	
Brand	ALab™ by ACS Material
Model	SP-XUV5101
SKU #	ALSPX100
Optical System	Double Beam
Wavelength Range	190–1100 nm
Spectral Bandwidth	1.0nm
Wavelength Accuracy	±0.1nm (at 656.1nm), ±0.3nm full range
Wavelength Repeatability	≤0.1nm
Photometric Accuracy	±0.0015A(0–0.5A) ±0.002A(0.5A–1A)
Photometric Repeatability	±0.001A(0–0.5A) ±0.0015A(0.5A–1A)
Photometric Range	-0.3–3A, 0–9999C(0–9999F)
Stray Light	≤0.02%T @ 220,360nm
Stability	≤0.001 A/h / 500nm
Baseline Flatness	±0.001A
Noise	0.0005A@500nm
Work Mode	T, A, C, E
Scanning Speed	High Medium Slow
Wavelength Setting	Auto
Display	10.1-inch large color touch screen(1024×600)
Light Source	Hamamatsu Xenon Lamp (Japan)
Detector	Imported Silicon Photodiode
Cuvette Holder	Single hole 1cm holder (standard for double beam)
Output	USB Port, Printer Port
Power Requirements	110/220V, 50/60Hz, 120W
Dimension[L×W×H]	570mm×440×210mm
Weight	20kg

Accessories — SP-XUV5101

Accessories	
Item no.	Description
18901008	1mm(H) * 10mm(W) * 30mm(L) (for SP-UV3101/SP-UV3102/SP-XUV5101/SP-XUV5102)
18901009	Single hole 1cm holder (for SP-UV3101/SP-UV3102/SP-XUV5101/SP-XUV5102)
18901010	Single hole 5cm holder(1cm-10cm) (for SP-UV3101/SP-UV3102/SP-XUV5101/SP-XUV5102)
18902200	Automatic 8-position cell holder 1cm (for SP-UV3101/SP-UV3102/SP-XUV5101/SP-XUV5102)
18901509	Visible light precision filter 440, 546, 635nm (for full series)
18901510	UV-K2Cr2O7 235, 257, 313, 350nm (for full series)
18901511	HOMIUM 241, 361, 417, 538, 641nm (for full series)
18901512	Stray light filter 220nm (for full series)
18901513	Stray light filter 360nm (for full series)

Scope of delivery

- **Standard configuration:** 10mm glass cuvette x 4, 10mm quartz cuvette x 2, power cord, user's manual, PC software.
- **Listed accessories:** see the Accessories table for item numbers and descriptions.

SECTION IV**Applications**

The SP-XUV5101 is listed with photometric measurement, quantitative measurement, kinetics, spectrum scan, DNA\Protein test and multi-wavelength test; optional accessories extend the application range for common samples and special ones.

Product value: a 10.1-inch capacitive touch screen with a windows graphic interface, 1.0nm spectral bandwidth, 1024M in-house memory, USB data transfer with export to Excel, and a range of optional accessories.

Revision Date: 10/17/2026

DISCLAIMER

ALab™ is a trademark of ACS Material, LLC. ACS Material, LLC believes that the information in this Technical Data Sheet is accurate and represents the best and most current information available to us. ACS Material makes no representations or warranties, either express or implied, regarding the suitability of the equipment for any application or the accuracy of the information contained within this document. Specifications are typical and may vary; confirm product details and application suitability at the time of quotation. Accordingly, ACS Material will not be responsible for damages resulting from use of or reliance upon this information.